



S51003 Series 140/200 w C Band SSPAs

	Range	Units	Notes
Electrical Specifications			
Frequency	5.850-6.425	GHz	
Gain	54 min., 56 typ.	dB	
Gain Flatness			
Full Band	+/-1.5max.	dB	
Per 40 MHz Segment	+/-0.20	dB	
Gain Stability vs. temperature	+/-2.0	dB	
P_{1dB}^{-1}			
-052	51.2 min., 51.5 typ.	dBm	
-053	52.2 min., 52.5 typ.	dBm	
P_{sat}^{-1}			
-052	+52 typ.	dBm	
-053	+53 typ.	dBm	
Third Order Intermodulation Distortion	-25 max.	dBc	@3 dB backoff relative to rated P_{1dB}
VSWR			
Input/Output	1.35/1.30 max.	:1	
Power Requirement			
Input Voltage	+11 to +13	vdc	
Current			
-052	62 nom.	A	
-053	74 nom.	A	
Mechanical Specifications			
Outline (incl. output isolator)	5.0 x 15.25 x 1.53 (127 x 387 x 38.9)	in. (mm)	L X W X H
Weight (approximate)	6.6 (3)	lbs. (kg)	
Connectors			
RF Input	SMA	Female	N Female optional
RF Output	CMR137 Cover Flange		
Power	Threaded RFI Filter		
Fault/Control	MS3112E12-8P or 15 Pin D		Optional
Environmental			
Operating Baseplate Temperature	-40 to +60	°C	
Humidity	100	%	without condensation

Notes:

1. Extended band (5.85-6.725 GHz, S51403 series) available.
2. Derate power linearly by 1.0 dB from 6.425 to 6.725 GHz with extended band option.

Options:

- Option 1: Type N Female Input connector
- Option 2: N/A
- Option 3: Control I/O (mute, fault alarm, temperature indication)
- Option 4: Detected RF Output (+4 V nom. @ P1dB)
- Option 5: RF Sample Port (-40 dBc nom., SMA Female conn.)
- Option 6: Manual Gain Adjust (20 dB range, continuous)

Specifications are subject to change at the discretion of Locus Microwave, Inc.

176 Technology Dr., Suite 200, Boalsburg, PA 16827 USA • Tel: +1 814 466 6275 • Fax: +1 814 466 1104

www.locusmicrowave.com