

## Model Number Configuration Guide

Construct part number as follows:

**UB61000 - \_ \_ \_ , Options**

**Output Frequency:**

0 = 7.90-8.40 GHz



**Output Power:**

050 = 100 watts



### Options:

**Opt. 1G:** Paint color, Green per Fed Std 595 chip 34094, (White Standard)

**Opt. 1T:** Paint color, Tan per Fed Std 595 chip 33446, (White Standard)

**Opt. 2:** N/A

**Opt. 3:** CPR112G waveguide output flange (WR112 Cover Flange standard)

**Opt. 4:** N/A

**Opt. 5:** N/A

**Opt. 6:** N/A

**Opt. 7:** 110/220 VAC operation (48 VDC standard)

**Opt. 8:** Internal 10 MHz reference, 0.02 ppm stability (customer supplied external reference standard)

**Example: 100 watt, Green Paint, CPR112G Output, AC Powered**

**UB61000-050, Options 1G, 3, 7**

Please confirm configurations against product specifications, and with factory, prior to order.

176 Technology Dr., Suite 200, Boalsburg, PA 16827 USA • Tel: +1 814 466 6275 • Fax: +1 814 466 1104

08/09

[www.locusmicrowave.com](http://www.locusmicrowave.com)

CODAN SATCOM

